



LASER DRIVE

Laser Drive, Inc.
5318 Ranalli Drive
Gibsonia, Pa
15044
USA

Phone: (724) 443-7688
Fax: (724) 444-6430
www.laserdrive.com

Electrical Specification

Model 111
95-327 REV 0B

PARAMETER	MIN.	TYP.	MAX.	UNITS
Input Voltage <i>OPTION 1</i> <i>OPTION 2</i> <i>OPTION 3</i>	10 20 24	12 24 28	14 28 32	VDC
Input Current @ 10 VDC Input 2450VCD/6.5 mA Output			2.12	ADC
Starting Voltage	8		12	kV DC
Output Voltage* <i>RANGE 1</i> <i>RANGE 2</i> <i>RANGE 3</i>	1100 1500 1850		1500 1800 2450	VDC
Output Current* <i>RANGE 1</i> <i>RANGE 2</i> <i>RANGE 3</i>	3 4 6		4.5 5.5 6.5	mA DC
Output Current Ripple			2	% PK-PK
Efficiency		75		%
Operating Temperature	-20		+55	°C
Storage Temperature	-20		+60	°C
<p>Options: : (TTL) Enable The (TTL) enable should be connected to the ground-allowing unit to start laser. (Open Collector TTL). When not connected the unit will be disabled and the laser will be off.</p> <p>(CDRH) Delay of 3 to 7 seconds from when power is applied to the power supply until the laser tube fires.</p>				

* Additional voltages and currents are available. Call for information.

