

Remote Sens. **2012**, *4*, 561–582; doi:10.3390/rs4030561

OPEN ACCESS

Remote Sensing

ISSN 2072-4292

www.mdpi.com/journal/remotesensing

Article

Optimal Exploitation of the Sentinel-2 Spectral Capabilities for Crop Leaf Area Index Mapping

Katja Richter ^{1,*}, Tobias B. Hank ¹, Francesco Vuolo ², Wolfram Mauser ¹ and Guido D'Urso ³

¹ Department of Geography, Ludwig-Maximilians University Munich, Luisenstr. 37, D-80333 Munich, Germany; E-Mails: tobias.hank@lmu.de (T.H.); w.mauser@lmu.de (W.M.)

² Institute of Surveying, Remote Sensing and Land Information (IVFL), University of Natural Resources and Life Sciences (BOKU), Peter Jordan Str. 82, A-1190 Vienna, Austria; E-Mail: francesco.vuolo@boku.ac.at

³ Department of Agricultural Engineering and Agronomy, University of Naples Federico II, Via Università 100, I-80055 Portici, Italy; E-Mail: durso@unina.it

* Author to whom correspondence should be addressed; E-Mail: k.richter@iggf.geo.uni-muenchen.de; Tel.: +49-89-2180-6684.

Received: 20 January 2012; in revised form: 15 February 2012 / Accepted: 21 February 2012 / Published: 28 February 2012

Abstract: The continuously increasing demand of accurate quantitative high quality information on land surface properties will be faced by a new generation of environmental Earth observation (EO) missions. One current example, associated with a high potential to contribute to those demands, is the multi-spectral ESA Sentinel-2 (S2) system. The present study focuses on the evaluation of spectral information content needed for crop leaf area index (LAI) mapping in view of the future sensors. Data from a field campaign were used to determine the optimal spectral sampling from available S2 bands applying inversion of a radiative transfer model (PROSAIL) with look-up table (LUT) and artificial neural network (ANN) approaches. Overall LAI estimation performance of the proposed LUT approach (LUT_{N50}) was comparable in terms of retrieval performances with a tested and approved ANN method. Employing seven- and eight-band combinations, the LUT_{N50} approach obtained LAI RMSE of 0.53 and normalized LAI RMSE of 0.12, which was comparable to the results of the ANN. However, the LUT_{N50} method showed a higher robustness and insensitivity to different band settings. Most frequently selected wavebands were located in near infrared and red edge spectral regions. In conclusion, our results emphasize the potential benefits of the Sentinel-2 mission for agricultural applications.