



DATASHEET

FS-VCBOZ-4M (Bullet IP Camera)

4MP Indoor/Outdoor Varifocal Bullet IP Camera
With Infrared & Optical Zoom

Overview

The Varifocal Bullet IP Camera is a superior choice for both indoor and outdoor surveillance installations. With 1/3" OV High-resolution CMOS Sensor, it offers 4MP pixels for day or night use and are integrated with the Video software for powerful and flexible, integrated IP video management.

Key Features

- Up to 4 megapixel high resolution
- 2560 × 1440@20fps
- H.264, H.265
- Dual video streams
- DC 12 V & PoE (802.3af)
- Up to 60m IR range
- -S: Audio/Alarm IO
- Mobile Monitoring

Specification

Camera

Image Sensor	OV4689
Main processor	Hi3516D
Resolution	4MP
Effective Pixels	2688(H)*1520(V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec

S/N Ratio	≥52dB
Scanning System	Progressive

Video Output	Network
--------------	---------

LENS Type

Focus Length	2.8-12mm
--------------	----------

Focus Control	Auto
---------------	------

Lens Type	Auto
-----------	------

Pixels	5MP
--------	-----

Night Vision

Infrared LED	42μx 4PCS
--------------	-----------

Infrared Distance	60M
-------------------	-----

IR Status	Under 10 Lux By CDS
-----------	---------------------

IR Power On	CDS Auto Control
-------------	------------------

Network

Ethernet	RJ-45 (10/100Base-T)
----------	----------------------

Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
----------	---

ONVIF	Support ONVIF 2.4
-------	-------------------

P2P	Support QR Code
-----	-----------------

POE	Optional, Support IEEE 802.3af
-----	--------------------------------

WIFI	N/A
------	-----

Video Delay	0.3S (Within the Lan)
-------------	-----------------------

Main Stream 1	2560*1440@20fps
---------------	-----------------

Main Stream 2	2304*1296@30fps
Main Stream 3	1920*1080@30fps
Sub Stream 1	720*480@20fps 720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@20fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

Camera Features

Day/Nigh	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
ROI	Support
Defog Mode	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web

Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands
----------	--

General

Housing	Metal , IP66
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC 12V±10%, 1000mA
Dimension	275(W) x 91(H) x 80(D)mm
Weight	1400g

Accessories





 <https://www.fs.com>



The information in this document is subject to change without notice. FS has made all efforts to ensure the accuracy of the information, but all information in this document does not constitute any kind of warranty.