



Serinus[®] Cal 1000

Gas Dilution Calibrator

The Serinus Cal 1000* performs gas dilution calibrations and is used in conjunction with regulatory traceable gases and a zero air generator.

The most cost effective solution the Serinus Cal 1000 allows the most up-to-date calibrations technology to be available to all.

* Acoem Serinus Cal 1000 formerly known as Ecotech Serinus Cal 1000

Features

- Performs single & multi-point calibrations using the Serinus Calibrator's precision mass flow controllers, for utmost confidence in the results
- Performs calibration manually through user interface or remotely via RS232, USB networks or digital inputs
- Designed & developed with wide-ranging customer input for easy, intuitive, accurate use.

Dilution & span flows

Dilution gas inputs:	1 standard 100 – 200 kPa (g) (2 optional)
Source gas inputs:	4 standard 100 – 200 kPa (g) (8 optional)
Dilution mass flow controller:	10 SLPM, 0 Deg, 1 ATM (std), 1 SLPM, 2 SLPM, 5 SLPM or 20 SLPM (optional), 2nd MFC (optional)
Source mass flow controller:	50 SCCM, 0 Deg, 1 ATM (std), 10 SCCM, 20 SCCM, 100 SCCM, 500 SCCM or 1 SLPM, 2 SLPM (optional), 2nd MFC (optional)
Flow accuracy (constant temp):	Within 1 % of full scale
Flow repeatability:	Within 0.15 % of full scale
Linearity:	Within 0.15 % of full scale
Operating gas pressure:	100 – 200 kPa
Zero drift:	< 0.6 % per year
Response time:	< 5 seconds
Output manifold:	4 output ports standard
Dilution ratio:	Variable 10:1 to 2000:1 (std configuration)
Case dimensions rack length:	597 mm (23.5") (front to rear)
Total length (with latch release):	638 mm (25.1")
Chassis width:	418 mm (16.5")
Front panel width:	429 mm (16.9")
Chassis height:	163 mm / uses 4RU (6.4")
Front panel height:	175 mm (6.9")
Weight:	18.2 kg

Communication

User interface:	Via front panel keypad or computer
Programmable calibrations:	16 separate programmable sequences 32 separate programmable points
Analog input:	Three analog voltage inputs (0 - 5 VDC) CAT I rated
Digital output:	RS232 port #1: Normal digital communication RS232 port #2: Multidrop port used for multiple analyzer connections on a single RS232 USB port connection on rear panel 25 pin connector with discrete status & user control USB stick memory (front panel) for data logging, event logging & parameter storage 8 Digital Outputs, open collector max 400 mA each at 12 VDC (max total output 2A) 8 Digital Inputs, 0 - 5 VDC CAT I rated 1 Diluent Control, + 12 V output.

Power

Operating voltage:	100 - 240 V VAC 50 / 60 Hz (autoranging)
Power consumption:	165 VA maximum (typical at start-up) 95 VA after warm-up
Operating conditions ambient temperature range:	0 - 45 °C (32 - 104 °F), 20 - 35 °C for optimum performance
Pressure:	Maximum altitude: 3000 m above sea level.

This page is intentionally blank

