Holistic HMI Design for Automated Vehicles: Bridging In-Vehicle and External Communication

HAOYU DONG*, Eindhoven University of Technology, Netherlands

TRAM THI MINH TRAN*, Design Lab, The University of Sydney, Australia

PAVLO BAZILINSKYY, Eindhoven University of Technology, Netherlands

MARIUS HOGGENMÜLLER, Design Lab, The University of Sydney, Australia

DEBARGHA DEY, Information Sciences, Cornell Tech, United States

SILVIA CAZACU, Katholieke Universiteit Leuven, Belgium

MERVYN FRANSSEN, Eindhoven University of Technology, Netherlands

RUOLIN GAO, Eindhoven University of Technology, Netherlands

As the field of automated vehicles (AVs) advances, it has become increasingly critical to develop human-machine interfaces (HMI) for both internal and external communication. Critical dialogue is emerging around the potential necessity for a holistic approach to HMI designs, which promotes the integration of both in-vehicle user and external road user perspectives. This approach aims to create a unified and coherent experience for different stakeholders interacting with AVs. This workshop seeks to bring together designers, engineers, researchers, and other stakeholders to delve into relevant use cases, exploring the potential advantages and challenges of this approach. The insights generated from this workshop aim to inform further design and research in the development of coherent HMIs for AVs, ultimately for more seamless integration of AVs into existing traffic.

CCS Concepts: • Human-centered computing → Interaction design.

Additional Key Words and Phrases: automated vehicles; human-machine interfaces; design thinking; participatory design

1 BACKGROUND

The widespread adoption of automated vehicles (AVs) hinges on effective communication with not only internal users, such as drivers and passengers, but also external road users, including pedestrians, cyclists, and manual car drivers [3, 5, 6, 8, 15, 17]. Effective communication is crucial for ensuring safety and seamless integration of AV into the existing traffic ecosystem [4]. In this context, there has been extensive research regarding the design of human-machine interfaces (HMIs) for AVs, often focusing either on internal interfaces (iHMIs) or external interfaces (eHMIs). This reductionist approach simplifies the complex design space, excelling at addressing individual components of the system [1]—such as perfecting AV-to-driver or AV-to-pedestrian communications separately.

While the reductionist approach remains effective, current discourse suggests the need for a complementary holistic approach in HMI design for AVs [20]. This approach is particularly essential for designing for situations where multiple road users interact simultaneously with the AVs through either iHMIs or eHMIs or even both. By examining these interfaces concurrently, we can better understand their dynamics, thereby fostering a consistent experience for all stakeholders involved in the mixed traffic ecosystem [11].

Existing literature on holistic HMI design for AVs remains sparse, with few related works. For example, Bengler et al. [4] proposed a framework that encompasses various HMI types (including dynamic HMI (dHMI), vehicle HMI, infotainment HMI, automation HMI, and external HMI), emphasising the importance of dHMI in communicating simultaneously with in-vehicle users and other road users.

1

^{*}Both authors contributed equally to this research.

Building on the concept of dHMI, consider an AV equipped with an interactive lighting system as an example of a holistic HMI design. For instance, when the AV is about to make a turn or stop, the external lights would flash in a specific pattern to signal its intention to other road users (e.g., [7]). Simultaneously, an internal display would mirror this pattern, informing the passengers about the AV's upcoming actions (e.g., [19]). This way ensures consistent information being shared with all involved parties.

However, the holistic HMI approach goes beyond information mirroring. It also involves providing a coherent design language and user experience that caters to the fluid roles that individuals play in the traffic environment. For instance, an individual may transition from being a pedestrian to a passenger in an AV and later interact with AVs as a manual car driver. Even within these roles, the nature of interaction with the AVs can vary, depending on different perspectives. For example, drivers may be considered as both internal and external users, depending on whether they are operating their own vehicles or interacting with AVs. Recent studies have explored the use of eHMIs to communicate with conventional drivers [13, 15, 16] as well as conducted comparative analyses on the use of eHMIs and iHMIs for communication with these drivers [2, 12]. This dual role of drivers suggests the potential implication for a design approach that ensures a high degree of compatibility between eHMIs and iHMIs.

Given the complexity of roles and the potential benefits of a holistic HMI design approach, we see a timely opportunity for further exploration. As a starting point, we propose this workshop as a part of the AutomotiveUI conference.

2 WORKSHOP GOALS

The workshop is designed with two primary goals:

- (1) Exploring relevant use cases: Recognising that a holistic HMI design approach may not be necessary for every scenario, we will facilitate discussions to identify real-world use cases and scenarios where adopting such an approach could be advantageous.
- (2) Building community: We will bring together researchers and designers specialising in internal and external automotive HMIs, provoking discussion regarding existing design cases and concepts while encouraging the adoption of a broader perspective.

3 EXPECTED OUTCOMES

This workshop will serve as a foundational exploration of HMI for AV design and research through a holistic lens, cultivating a shared understanding among participants from various backgrounds. The insights derived from our discussions, particularly regarding use cases and validity arguments for this holistic approach, will be compiled in a summary report. We intend to disseminate these findings through an academic article, marking the first consensus among experts in the field.

4 WORKSHOP OVERVIEW

Our target participants include designers, engineers, and researchers with expertise in automotive HMI design and development, encompassing both in-vehicle and external interfaces. Additionally, we welcome individuals with other profiles, including urban planners, traffic policymakers, etc., to promote interdisciplinary collaboration.

In order to effectively support the discussion among participants from different backgrounds, we will conduct a deliberately designed collaborative activity known as *participatory physicalisation* [9, 10, 18]. This activity employs

detailed instructions and tangible artefacts to facilitate the exploration of ideas, physicalise the discussion process and lead to shared understandings [14].

We anticipate hosting approximately 30 participants for a well-rounded and insightful session.

4.1 Pre-Workshop Plan

The workshop call will be shared across social media platforms like Twitter and LinkedIn 1.5 months prior to the event. To further promote the workshop, organisers will leverage academic and industry networks and encourage attendees to share details within their professional circles.

Participants will be requested to prepare a visual representation of their research topic, which may manifest in diverse forms, including prototype images, graphs or charts derived from their publication, or conceptual frameworks or models. These materials serve a twofold purpose: firstly, to offer a clear depiction of each participant's work, and secondly, to facilitate the creation of physicalisation during the collaborative activity proposed for this workshop. The participants can print the visual representation by themselves, or they could submit the file to the organisers prior to the workshop.

4.2 Workshop Activities

The workshop will span over a duration of 3 to 3.5 hours with designed activities to achieve the goals (see Table 1).

Activity	Time
Opening & Introduction	10 min
Keynote	30 min
Coffee break	15 min
Participatory Physicalisation - Part 1	45 min
Coffee break	15 min
Participatory Physicalisation - Part 2	45 min
Closing	30 min

Table 1. Tentative schedule activities of the workshop

- 4.2.1 *Opening & Introduction.* The workshop will begin with the organisers' introductions and a presentation of the workshop's objectives, schedule of activities and expected outcomes.
- 4.2.2 Keynote. We will host two distinct guest speakers—one specialising in iHMIs and the other in eHMIs, to present overviews of the state-of-the-art research in their respective fields.
- 4.2.3 Participatory Physicalisation. This activity consists of two parts separated by a short coffee break.
 - Part 1 Group Discussions: Participants will be divided into groups of five and engage in a series of timed discussions. Each group will be guided by one of the organising members. The discussions aim to brainstorm potential real-world scenarios where it is crucial to consider both internal and external user perspectives when designing HMIs. To aid these discussions, we will provide basic prototyping tools such as sticky notes, tapes, pencils, and markers. The printed visual representation will be used in this discussion. In addition, unique tangible items, purposefully crafted for this workshop, will be available to stimulate the brainstorming process. The purpose of the tangible items is to provide a physicalisation of the collaborative discussion in order to aid discourse building and scenario exploration.

3

• Part 2 - Plenary Presentations: After the group discussions, all participants will join together and each group will present their discussion summaries using the physicalisation as a reference. In this way, we aim to create connections that go beyond previously created groups, identifying points of alignment and friction that contribute to future research directions in holistic HMI design.

5 ORGANISERS

Haoyu Dong, corresponding author, is a doctoral candidate at the Eindhoven University of Technology in the Department of Industrial Design. Her research follows Research through Design approach and focuses on interaction design research of in-vehicle users and AVs, specifically in non-critical scenarios.

Tram Thi Minh Tran is a doctoral candidate in the Urban Interfaces Lab at the University of Sydney's School of Architecture, Design, and Planning. Her research investigates the intricate interactions between pedestrians and AVs in complex traffic scenarios involving multiple road users.

Pavlo Bazilinskyy is an assistant professor at Eindhoven University of Technology focusing on AI-driven interaction between AVs and other road users. He finished his PhD at TU Delft in auditory feedback for automated driving as a Marie Curie Fellow, where he also worked as a postdoc. He was the head of data research at SD-Insights. Pavlo is a treasurer of the Marie Curie Alumni Association (MCAA).

Marius Hoggenmüller is a Lecturer in Interaction Design in the Design Lab at the University of Sydney's School of Architecture, Design, and Planning. His work focuses on prototyping interactions with emerging technologies in cities, such as urban robots and autonomous systems.

Debargha Dey is a postdoctoral researcher at Cornell Tech, with a research focus on human-automation interaction. He has 8+ years of experience in the domain of human factors for automated driving and traffic behaviour.

Silvia Cazacu is a doctoral candidate at the Spatial Applications Division Leuven of KU Leuven, Belgium. Her research focuses on participatory physicalisation as an approach to support collaboration in data ecosystems and draws on critical data studies and data humanism.

Mervyn Franssen is a doctoral candidate at the Eindhoven University of Technology in the Department of Industrial Design. His research is focused on designing and validating natural interfaces and behavioural characteristics for automation systems in order to reduce uncertainty and avoid unpredictable behaviour for human operators who sometimes need to take control.

Ruolin Gao is a doctoral candidate in the Department of Industrial Design, Eindhoven University of Technology. She focuses on the interaction between AVs and manually-driven vehicles to foster smooth interaction in a mixed-traffic environment.

REFERENCES

- [1] Russell L. Ackoff. 1973. Science in the Systems Age: Beyond IE, OR, and MS. Oper. Res. 21 (1973), 661–671.
- [2] Lilit Avetisyan, Aditya Deshmukh, X Jessie Yang, and Feng Zhou. 2023. Investigating HMIs to Foster Communications between Conventional Vehicles and Autonomous Vehicles in Intersections. arXiv preprint arXiv:2305.17769 (2023).
- [3] Hüseyin Avsar, Fabian Utesch, Marc Wilbrink, Michael Oehl, and Caroline Schießl. 2021. Efficient communication of automated vehicles and manually driven vehicles through an external Human-Machine Interface (eHMI): Evaluation at T-junctions. In HCI International 2021-Posters: 23rd HCI International Conference, HCII 2021, Virtual Event, July 24–29, 2021, Proceedings, Part III 23. Springer, 224–232.
- [4] Klaus Bengler, Michael Rettenmaier, Nicole Fritz, and Alexander Feierle. 2020. From HMI to HMIs: Towards an HMI framework for automated driving. Information (Switzerland) 11 (2 2020). Issue 2. https://doi.org/10.3390/info11020061
- [5] Mark Colley, Tim Fabian, and Enrico Rukzio. 2022. Investigating the Effects of External Communication and Automation Behavior on Manual Drivers at Intersections. *Proc. ACM Hum.-Comput. Interact* 6 (2022), 1–16.

- [6] Debargha Dey, Azra Habibovic, Andreas Löcken, Philipp Wintersberger, Bastian Pfleging, Andreas Riener, Marieke Martens, and Jacques Terken.
 2020. Taming the eHMI jungle: A classification taxonomy to guide, compare, and assess the design principles of automated vehicles' external human-machine interfaces. Transportation Research Interdisciplinary Perspectives 7 (2020), 100174.
- [7] Ford Motor Corporation. 2017. Ford, Virginia Tech Go Undercover to Develop Signals That Enable Autonomous Vehicles to Communicate with People. https://media.ford.com/content/fordmedia/fna/us/en/news/2017/09/13/ford-virginia-tech-autonomous-vehicle-human-testing.html
- [8] Kai Hollander, Mark Colley, Enrico Rukzio, and Andreas Butz. 2021. A taxonomy of vulnerable road users for hci based on a systematic literature review. In Conference on Human Factors in Computing Systems - Proceedings. https://doi.org/10.1145/3411764.3445480
- [9] Samuel Huron, Pauline Gourlet, Uta Hinrichs, Trevor Hogan, and Yvonne Jansen. 2017. Let's Get Physical: Promoting Data Physicalization in Workshop Formats. In Proceedings of the 2017 Conference on Designing Interactive Systems (Edinburgh, United Kingdom) (DIS '17). Association for Computing Machinery, New York, NY, USA, 1409–1422. https://doi.org/10.1145/3064663.3064798
- [10] Yvonne Jansen, Pierre Dragicevic, Petra Isenberg, Jason Alexander, Abhijit Karnik, Johan Kildal, Sriram Subramanian, and Kasper Hornbæk. 2015. Opportunities and Challenges for Data Physicalization. In Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems (Seoul, Republic of Korea) (CHI '15). Association for Computing Machinery, New York, NY, USA, 3227–3236. https://doi.org/10.1145/2702123.2702180
- [11] Evangelos Karapanos. 2013. Modeling Users' Experiences with Interactive Systems. https://doi.org/10.1007/978-3-642-31000-3
- [12] Yang Li, Hailong Liu, and Barbara Deml. 2021. Manually Driven Vehicle Encounters with Autonomous Vehicle in Bottleneck Roads: HMI Design for Communication Issues. In Proceedings of the 9th International Conference on Human-Agent Interaction (Virtual Event, Japan) (HAI '21). Association for Computing Machinery, New York, NY, USA, 382–385. https://doi.org/10.1145/3472307.3484678
- [13] Shiva Nischal Lingam, Joost de Winter, Yongqi Dong, Anastasia Tsapi, Bart van Arem, and Haneen Farah. 2022. eHMI on the Vehicle or Just a Traffic Light? A Driving Simulator Study. (2022).
- [14] Georgia Panagiotidou, Jeroen Poblome, Jan Aerts, and Andrew Vande Moere. 2022. Designing a Data Visualisation for Interdisciplinary Scientists. How to Transparently Convey Data Frictions? Computer Supported Cooperative Work (CSCW) 31 (2022), 633–667. Issue 4.
- [15] Vassilis Papakostopoulos, Dimitris Nathanael, Evangelia Portouli, and Angelos Amditis. 2021. Effect of external HMI for automated vehicles (AVs) on drivers' ability to infer the AV motion intention: A field experiment. Transportation research part F: traffic psychology and behaviour 82 (2021), 32–42
- [16] Michael Rettenmaier, Deike Albers, and Klaus Bengler. 2020. After you?!-Use of external human-machine interfaces in road bottleneck scenarios. Transportation research part F: traffic psychology and behaviour 70 (2020), 175–190.
- [17] Wilbert Tabone, Joost De Winter, Claudia Ackermann, Jonas Bärgman, Martin Baumann, Shuchisnigdha Deb, Colleen Emmenegger, Azra Habibovic, Marjan Hagenzieker, Peter A Hancock, et al. 2021. Vulnerable road users and the coming wave of automated vehicles: Expert perspectives.

 Transportation research interdisciplinary perspectives 9 (2021), 100293.
- [18] Rosa van Koningsbruggen, Hannes Waldschütz, and Eva Hornecker. 2022. What is Data? Exploring the Meaning of Data in Data Physicalisation Teaching. In Sixteenth International Conference on Tangible, Embedded, and Embodied Interaction (Daejeon, Republic of Korea) (TEI '22). Association for Computing Machinery, New York, NY, USA, Article 13, 21 pages. https://doi.org/10.1145/3490149.3501319
- [19] Marc Wilbrink, Anna Schieben, and Michael Oehl. 2020. Reflecting the automated vehicle's perception and intention: Light-based interaction approaches for on-board HMI in highly automated vehicles. In *Proceedings of the 25th International Conference on Intelligent User Interfaces Companion*.
- [20] John Zimmerman, Jodi Forlizzi, and Shelley Evenson. 2007. Research Through Design as a Method for Interaction Design Research in HCI. CHI