

SALES SPECIFICATIONS

Sales Specification No : 02004-6

Effective Date : 04/24/2017

Page No. 1 of 1

EASTMAN**PRODUCT NAME****Eastman(TM) Liquid Ethylene****SPECIFICATIONS**

PROPERTY	LIMITS	TEST METHOD
Ethylene, mol%	99.900 MIN	TXAL-A-XX-G-GC-440
Carbon Monoxide, molppm	5 MAX	TXAL-A-XX-G-GC-440
Carbon Dioxide, molppm	5 MAX	TXAL-A-XX-G-GC-440
Hydrogen, molppm	5 MAX	TXAL-A-XX-G-GC-440
Methane, molppm	500 MAX	TXAL-A-XX-G-GC-440
Ethane, molppm	500 MAX	TXAL-A-XX-G-GC-440
Methane plus Ethane, molppm	1000 MAX	TXAL-A-XX-G-GC-440
Acetylene, molppm	5 MAX	TXAL-A-XX-G-GC-440
C3 and Heavier, molppm	100 MAX	TXAL-A-XX-G-GC-440
Methanol, ppm	3 MAX	TXAL-A-XX-G-GC-180
Water, ppm	5 MAX	TXAL-A-XX-G-PTM-002
Oxygen, molppm	5 MAX	TXAL-A-XX-G-PTM-003
Sulfur, molppm	1 MAX	ASTM D4468

EastmanTM is a trademark of Eastman Chemical Company.

Eastman Chemical Company · P.O. BOX 511 · Kingsport, Tennessee 37662 USA · 1-800-EASTMAN · 1-423-229-2000 · www.EASTMAN.com

Sales Specification available on Eastman.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.