

SALES SPECIFICATIONS

Sales Specification No : 31869-4
Effective Date : 02/02/2019
Page No. 1 of 1

EASTMAN**PRODUCT NAME****Eastman BioExtend(TM) 30HP Antioxidant Solution****SPECIFICATIONS**

PROPERTY	LIMITS	TEST METHOD
MTBHQ, %	28.5 - 31.5	TCMD-A-AN-G-GC-875
Appearance	PASS	TCMD-A-AN-G-MIS-31

The appearance of Eastman BioExtend(TM) 30HP can vary from a yellow/amber to a dark, brownish-red solution, but will be free from haze or insoluble matter. Metal chelator is added at time of manufacture.

The oxidative stability of biodiesel fuel is influenced by many factors including raw material selection, manufacturing process, antioxidant selection and timing of antioxidant addition. For maximum performance, it is recommended that BioExtend(TM) 30HP be added promptly after manufacture of biodiesel.

Eastman Chemical Company · P.O. BOX 511 · Kingsport, Tennessee 37662 USA · 1-800-EASTMAN · 1-423-229-2000 · www.EASTMAN.com

Sales Specification available on Eastman.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.