

Advances in Weightless Neural Systems

F.M.G. França,¹ M. De Gregorio,³ P.M.V. Lima,² W.R. de Oliveira⁴

1 – COPPE, 2 – iNCE, Universidade Federal do Rio de Janeiro, BRAZIL

3 - Istituto di Cibernetica “E. Caianiello” – CNR, Pozzuoli, ITALY

4 – Universidade Federal Rural de Pernambuco, BRAZIL

Abstract. Random Access Memory (RAM) nodes can play the role of artificial neurons that are addressed by Boolean inputs and produce Boolean outputs. The *weightless* neural network (WNN) approach has an implicit inspiration in the decoding process observed in the dendritic trees of biological neurons. An overview on recent advances in weightless neural systems is presented here. Theoretical aspects, such as the VC dimension of WNNs, architectural extensions, such as the Bleaching mechanism, and novel quantum WNN models, are discussed. A set of recent successful applications and cognitive explorations are also summarized here.

1 From n -tuples to artificial consciousness

It has been 55 years since Bledsoe and Browning [20] introduced the n -tuple classifier, a binary digital pattern recognition mechanism. The pioneering work of Aleksander on RAM-based artificial neurons [1] carried forward Bledsoe and Browning's work and paved the path of weightless neural networks: from the introduction of WiSARD (Wilkes, Stonham and Aleksander Recognition Device) [2][3], the first artificial neural network machine to be patented and commercially produced, into the 90's, when new probabilistic models and architectures, such as PLNs, GRAMs and GNUs, were introduced and explored [4][5][6][7][8][9]. A natural drift into cognitive and conscious architectures followed, due to the work of Aleksander and colleagues [10][11][12][13][14][15]. A brief but more detailed history of weightless neural systems can be found in [16].

While Braga proposed a geometrical and statistical framework to model the state space of pattern distribution in the n -dimensional Boolean space [22], Bradshaw introduced the use of statistical learning theory tools in the analysis of the n -tuple classifier and related weightless neural models [23]. Interestingly, Bradshaw found out that the VC dimension of the n -tuple classifier suggests much poorer generalization capabilities than found in practice, which also motivated the production of the effective VC dimension for this weightless model [24][25]. The high VC dimension of the n -tuple classifier looks underexplored since saturation of RAM nodes contents often happens if a relatively small n value is chosen, i.e., when the size of the training set is large enough to allow for writing 1's in most of the RAM nodes positions. The introduction of the *bleaching* mechanism [40][56] was possible via extending RAM nodes from one-bit positions to counters able to register the number of times a particular RAM position was accessed during the training phase. This extension follows early probabilistic weightless models, such as PLNs and GRAMs, where RAM positions can also hold values different from 0's and 1's that are interpreted as firing probabilities. In the next section, bleaching is explained together

with how it is related with “mental” images [26][55] produced by the DRASiW model [48][81].

Section 3 summarizes how quantum computing [66] can be regarded as the mathematical quantisation of (classical) Boolean logic computing. Truth values (bits) are regarded as an orthonormal basis (cbits) of a two dimensional complex vector space where an arbitrary vector is called qubits, multiple bits are tensor products of cbits and Boolean operators are realised as unitary matrix. A RAM-based neural network, a universal Boolean realiser, is then trivially quantised into a q-RAM-based neural network [67][68][69]. Section 4 concludes this paper.

2 “Mental” images and Bleaching

DRASiW is an extension to the WiSARD model provided with the ability of producing pattern examples, or prototypes, derived from learned categories [26] [48][81]. RAM-discriminators are modified in what their memory locations may hold and, correspondingly, in their training algorithm. Similarly to PLN nodes, introduced by Aleksander [4], such change allows one to store m -bit words in memory locations, and such can be exploited in the generation of “**mental**” images of learned pattern categories, i.e., to be able to produce prototypes [56].

It is possible that some of the “mental” images produced by DRASiW are contour-saturated images, predominantly composed by dark grey/black pixels. In such a scenario, WiSARD’s discriminators generate ambiguous responses, i.e., draws between true and false winner responses. This is due to the saturation that (i) is quickly reached for a training set with a relevant number of class examples and (ii) occurs in an inverted order of the size of RAM neurons: smaller RAM neurons get saturated (most RAM positions written) sooner as the number of patterns used in the training phase increases.

By taking advantage of DRASiW’s prototype generation capability, one can avoid ambiguous discriminator responses. Consider the introduction of an integer variable threshold b , $b \geq 1$, over all RAM neurons contents at all discriminators. At the start of a pattern test, $b = 1$ and, if one observes a draw between discriminator responses, b is incremented and the discriminators outputs are re-calculated taking into account only RAM neuron contents above b . A straightforward convergence policy, called **bleaching**, is to have b incremented until just one of the discriminators producing a winner response. Notice that this process is directly related to the way pattern examples are produced from “mental” images in the DRASiW internal retina. Furthermore, based on the “mental” image threshold idea to generate a prototype, it was shown in [56] that, by re-evaluating the set of RAM-discriminator responses upon the detection of a draw, higher rates of correct classification could be obtained.

The improvement of WiSARD’s learning mechanism has allowed us to successfully implement new applications of weightless system in those domains that would not have been tackled without the changes introduced [30][32][35][36][37][40] [44].

The most interesting and recent application of the conjunct use of both mental images and bleaching is a WiSARD-based approach for non-rigid deformable object tracking [54]. The proposed approach allows deploying an on-line training on the texture and shape features of the object, to adapt in real-time to changes, and to

partially cope with occlusions. In Figure 1 sketches of the WiSARD tracking results are reported.




Fig. 1: Tracking and “mental” image adaptation during pizza making process

3 Quantum Weightless Models

The mathematical quantisation of the Boolean logic is an embedding of the classical bits $\mathbf{B} = \{0,1\}$, the field of integers modulus 2, in a convenient Hilbert space. A natural way of doing this is to represent them as an orthonormal basis of a Complex Hilbert space. Linear combinations of the basis span the whole space whose elements, called states, are said to be in superposition. Any basis can be used but in Quantum Computing it is customary to use the canonical one as column vectors: $|0\rangle = [1 \ 0]^T$ and $|1\rangle = [0 \ 1]^T$. In this context these basis elements are called the computational-basis states. A general state of the system, a vector $|\varphi\rangle = [\alpha \ \beta]^T$, can be written as: $|\varphi\rangle = \alpha|0\rangle + \beta|1\rangle$, where α, β are complex numbers, called *probability amplitudes* when constrained by the normalisation condition: $|\alpha|^2 + |\beta|^2 = 1$. This is the model of one *qubit*. Multiple qubits are obtained via tensor products. A common notation for tensor on the basis: $|i\rangle \otimes |j\rangle = |ij\rangle$, where $i, j \in \{0,1\}$. The values stored in a PLN Node 0, 1 and u are, respectively, represented by the qubits $|0\rangle, |1\rangle$ and $\mathbf{H}|0\rangle$, where \mathbf{H} is the Hadarmard matrix defined as $\mathbf{H}|0\rangle = 1/\sqrt{2}(|0\rangle + |1\rangle)$ and $\mathbf{H}|1\rangle = 1/\sqrt{2}(|0\rangle - |1\rangle)$. The probabilistic output generator of the PLN are represented as measurement of the corresponding qubit. There is an obvious relationship between outputs of a PLN and that of a q-PLN that associates i to $|i\rangle$, where $i = 0, 1$ and u to $\mathbf{H}|0\rangle$, resulting 0 or 1 with probability $1/2$. The random properties of the PLN are guaranteed to be implemented by measurement of $\mathbf{H}|0\rangle$ from the quantum mechanics principles (see e.g. Section 2.2 and Chapter 8 of [66] for a lengthier discussion). Another useful unitary matrix is the quantum not: $\mathbf{X}|0\rangle = |1\rangle$ and $\mathbf{X}|1\rangle = |0\rangle$. A quantum weightless neural networks is simply [67][68]: $N = \sum_{x \in \mathbf{B}^n} A_x |\alpha_x\rangle \langle x|$ where \mathbf{B}^n can be seen as the set n -bits strings, has a very interesting interpretation which relates it to a a sort of generalised look up table or

RAM memory: the action of N on a basis element $|x\rangle$ returns $A_x|\alpha_x\rangle$ which can be interpreted as the content of the memory location addressed by x (or $|x\rangle$), where A_x is an arbitrary unitary matrix for each x and $|\alpha_x\rangle$ is an m -qubit. In the case of a q-PLN, each A_x is one of the unitary matrices **I**, **X** or **H** and $|\alpha_x\rangle = 0$. Whilst for the q-MPLN, each A_x is of the form: $A_p|0\rangle = \sqrt{1-p}|0\rangle + \sqrt{p}|1\rangle$ and $A_p|1\rangle = \sqrt{p}|0\rangle - \sqrt{1-p}|1\rangle$ and $|\alpha_x\rangle = 0$, where p is real number in the interval $[0, 1]$. This view of WNN is a novelty in [69]. Learning is to change the matrices A_x . This can be achieved by using controlling qubits (selectors). We refer the reader to [77][78][79] for further details on learning. This model is of sufficient generality as of being universal for quantum computation [80] and even more [69].

4 Final remarks

Recent applications based on the WiSARD n -tuple classifier showed competitive and/or matched state-of-art, but with training being performed orders of magnitude faster. Credit analysis [18], data stream clustering [35][36], indoor positioning [37], language POS-tagging [38], target tracking [46][54][64], face recognition [59], and recognition of HIV-1 subtypes [82] are among the problems tackled. Most of these applications made use of the *bleaching* [40][56] and other content write-frequency-based (e.g., [5]) disambiguating mechanisms.

The exploration of “mental images” in the WiSARD model in different problems such as rule extraction and tracking of shape-shifting targets constitute ongoing research work. On the cognitive perspective, where awareness remains as the mainstream interest, one should notice that research would be much harder if it couldn’t count with the agility of weightless neural systems. On the other hand, quantum extensions of the Boolean neuron [67][68] are also a natural and promising way to search for a much more powerful [69] neural computational paradigm.

References and Bibliography

- [1] I. Aleksander, Self-adaptive universal logic circuits, *IEE Electronic Letters*, 2, p. 321, August 1966.
- [2] I. Aleksander and T. J. Stonham, Guide to pattern recognition using random-access memories, *Computer and Digital Techniques*, 2, pp. 29-40, 1979.
- [3] I. Aleksander, W. Thomas, and P. Bowden, WISARD, a radical new step forward in image recognition, *Sensor Rev.*, 4(3), pp. 120-124, 1984.
- [4] I. Aleksander and W.W. Kan, A Probabilistic Logic Neuron Network for Associative Learning, *IEEE Proceedings of the First Int. Conf. on Neural Networks*, pp. 541-548, 1987.
- [5] I. Aleksander and C. Myers, Learning algorithms for probabilistic logic nodes, in: *Abstract of the First INNS88*, p 205, Boston, 1989.
- [6] I. Aleksander. Canonical neural nets based on logic nodes, in *Proc. of the IEE Int. Conf. on Artificial Neural Networks*, London, pp. 110-114, 1989.
- [7] I. Aleksander, *An introduction to neural computing*, Chapman and Hall, London, 1990.

- [8] I. Aleksander, Ideal neurons for neural computers, in: *Parallel Processing in Neural Systems and Computers*, North-Holland, Amsterdam, pp. 225-228, 1990.
- [9] I. Aleksander and H. Morton, General neural unit: retrieval performance, *IEE Electronics Letters*, 27, pp. 1176-1178, 1991.
- [10] I. Aleksander, Capturing consciousness in neural systems, in: *Artificial Neural Networks, 2. Proc. ICANN-92*, London: North-Holland, pp. 17-22, 1992.
- [11] I. Aleksander, *The World in My Mind My Mind in the World: Key Mechanisms of Consciousness in Humans Animals and Machines*, Imprint Academic, Exeter, 2005.
- [12] I. Aleksander: Machine consciousness. *Scholarpedia* 3(2): 4162 (2008)
- [13] I. Aleksander and H. Morton, Phenomenal weightless machines. *ESANN 2009*
- [14] I. Aleksander, Designing Conscious Systems. *Cognitive Computation* 1(1): 22-28 (2009)
- [15] I. Aleksander and D. Gamez, Iconic Training and Effective Information: Evaluating Meaning in Discrete Neural Networks. *AAAI Fall Symposium: Biologically Inspired Cognitive Architectures 2009*.
- [16] I. Aleksander, M. De Gregorio, F.M.G. Franca, P.M.V. Lima and H. Morton, A Brief introduction to Weightless Neural Systems. In: *17th European Symposium on Artificial Neural Networks, 2009, Bruges. Proc. of ESANN 2009*. Evere, Belgium: d-side, 2009. p. 299-305.
- [17] I. Aleksander and H. Morton, Back to Basics and Forward to Novelty in Machine Consciousness. *BICA 2012*: 1-6
- [18] D.S.F. Alves, D.O. Cardoso, H.C.C. Carneiro, F. M. G. Franca and P. M. V. Lima, An empirical study of the influence of data structures on the performance of VGRAM classifiers. In: *BRICS-CCI, 2013, Ipojuca, PE. Proc. of BRICS-CCI & CBIC 2013*, 2013. v. 1. p. 1-6.
- [19] P. Barros, W.R. de Oliveira and V. A. Torrea, Comparisons between Quantum and Classical Pattern Recognitions in DNA Sequence Analysis. In: *IV Workshop School in Quantum Computation and Information, 2012, Fortaleza. IV WECIQ, 2012*.
- [20] W.W. Bledsoe and I. Browning, Pattern Recognition and Reading by Machine, *Proceedings of the Eastern Joint Computer Conference*, Boston, pp. 225-232, 1959.
- [21] R. G. Bowmaker and G. G. Coghill, Improved recognition capabilities for goal seeking neuron, *IEE Electronics Letters*, 28, pp. 220-221, 1992.
- [22] A. de P. Braga and I. Aleksander, Geometrical treatment and statistical modelling of the distribution of patterns in the n-dimensional Boolean space. *Pattern Recognition Letters* 16(5): 507-515 (1995)
- [23] N.P. Bradshaw, *An Analysis of Learning in Weightless Neural Systems*, PhD thesis, Department of Electrical and Electronic Engineering, Imperial College London, September 1996.
- [24] N.P. Bradshaw and I. Aleksander: Improving the generalisation of the N-tuple classifier using the effective VC dimension. *Pattern Recognition Letters* 32(20): 1904-1905 (1996)
- [25] N.P. Bradshaw: The Effective VC Dimension of the n-tuple Classifier. *ICANN 1997*: 511-516.
- [26] E. Burattini, M. De Gregorio and G. Tamburrini: Mental Imagery in Explanations of Visual Object Classification. *SBRN 2000*: 137-143
- [27] E. Burattini, M. De Gregorio and A. de Francesco, NSL: a Neuro-Symbolic Language for Monotonic and Non-Monotonic Logical Inferences. *SBRN 2002*: 256-261, 2000
- [28] E. Burattini, M. De Gregorio and Guglielmo Tamburrini, NeuroSymbolic Processing: Non-Monotonic Operators and Their FPGA Implementation. *SBRN 2000*: 2-6
- [29] E. Burattini, M. De Gregorio, V.M.G. Ferreira and F.M.G. França, NSP: A Neuro-symbolic Processor. *IWANN (2) 2003*: 9-16, 2002
- [30] E. Burattini, Paolo Coraggio, Massimo De Gregorio: Agent WiSARD: A Hybrid System for

- Reconstructing and Understanding Two-dimensional Geometrical Figures. HIS 2003: 887-896
- [31] E. Burattini, A. de Francesco and M. De Gregorio, NSL: A Neuro-Symbolic Language for a Neuro-Symbolic Processor (NSP). *Int. J. Neural Syst.* 13(2): 93-101 (2003)
 - [32] E. Burattini, P. Coraggio, M. De Gregorio and M. Staffa, Agent WiSARD in a 3D World. *IWINAC* (2) 2005: 272-280
 - [33] E. Burattini, S. Rossi and M. De Gregorio, A Neural Network Generating Adaptive Rhythms for Controlling Behavior Based Robotic Systems. *SBRN* 2008: 15-20, 2007
 - [34] E. Burattini, M. De Gregorio and S. Rossi, An adaptive oscillatory neural architecture for controlling behavior based robotic systems. *Neurocomputing* 73(16-18): 2829-2836 (2010)
 - [35] D.O. Cardoso, M. De Gregorio, P.M.V. Lima, J. Gama, and F.M.G. França, Clustering data streams with weightless neural networks. *ESANN* 2011, Bruges p. 201-206.M.
 - [36] D.O. Cardoso, M. De Gregorio, P.M.V. Lima, J. Gama and F. M. G. França, A Weightless Neural Network-Based Approach for Stream Data Clustering. In: H. Yin , J.A.F. Costa and G. Barreto. (Org.). *A Weightless Neural Network-Based Approach for Stream Data Clustering*. Ed. Heidelberg: Springer, 2012, v. 7435, p. 328-335.
 - [37] D.O. Cardoso, J. Gama, M. De Gregorio, F.M.G. França, M. Giordano, P.M.V. Lima, WIPS: the WiSARD Indoor Positioning System. *ESANN* 2013, Bruges, p. 521-526.
 - [38] H.C.C. Carneiro, F.M.G. Franca and P.M.V. Lima, WANN-TAGGER: A Weightless Artificial Neural Network Tagger for the Portuguese Language. In: *International Conference on Neural Computation, 2010, Valencia. Proc. of the 2nd International Joint Conference on Computational Intelligence*. Lisboa: SciTePress Science and Technology Publications, 2010. p. 330-335.
 - [39] A. de Carvalho, M. C. Fairhurst and D. L. Bisset, Progressive learning algorithm for GSN feedforward neural architectures, *IEE Electronics Letters*, 30, pp. 506-507, 1994.
 - [40] D.S. Carvalho, H.C.C. Carneiro, F.M.G. França and P.M.V. Lima, B-bleaching: Agile Overtraining Avoidance in the WiSARD Weightless Neural Classifier. *ESANN* 2013, Bruges, p. 515-520.
 - [41] P. Coraggio and M. De Gregorio, WiSARD and NSP for Robot Global Localization, in: *Nature Inspired Problem-Solving Methods in Knowledge Engineering – Part II*, J. Mira & J.R. Alvarez eds., LNCS 4528 Springer, pp.449-458, 2005.
 - [42] P. Coraggio, M. De Gregorio, A Neurosymbolic Hybrid Approach for Landmark Recognition and Robot Localization. *BVAI* 2007: 566-575
 - [43] P. Coraggio and M. De Gregorio, WiSARD and NSP for Robot Global Localization. *IWINAC* (2) 2007: 449-458
 - [44] P. Coraggio, M. De Gregorio and M. Forastiere, Robot Navigation Based on Neurosymbolic Reasoning over Landmarks. *IJPRAI* 22(5): 1001-1014 (2008)
 - [45] V. M. G. Ferreira and F. M. G. França, Weightless implementations of weighted neural networks. In: *Anais do IV Simpósio Brasileiro de Redes Neurais*, pp. 53-54, 1997.
 - [46] H.L. França, J.C.P. da Silva, O. Lengerke, M.S. Dutra, M. De Gregorio and F.M.G. França, Movement pursuit control of an offshore automated platform via a RAM-based neural network. *ICARCV* 2010: 2437-2441
 - [47] D. Gamez and Igor Aleksander, Taking a Mental Stance Towards Artificial Systems. *AAAI Fall Symposium: Biologically Inspired Cognitive Architectures* 2009.
 - [48] M. De Gregorio, On the reversibility of multidiscriminator systems, Technical Report 125/97, Istituto di Cibernetica - CNR, Italy, 1997.
 - [49] M. De Gregorio, The Agent WiSARD Approach to Intelligent Active Video Surveillance Systems. *MVA* 2007: 331-334, 2005
 - [50] M. De Gregorio, A Hybrid Intelligent System for Active Video Surveillance. *ISDA* 2007: 21-26

- [51] M. De Gregorio, Active and reactive use of virtual neural sensors. ESANN 2008: 349-354
- [52] M. De Gregorio, An Intelligent Active Video Surveillance System Based on the Integration of Virtual Neural Sensors and BDI Agents, *IEICE Transaction on Information and Systems*, vol. E91-D, n. 7, pp. 1914-1921, 2008.
- [53] M. De Gregorio, A. Rullo and S. Rubinacci, ISIDIS: an intelligent videosurveillance system. *AVI* 2012: 800-801
- [54] M. De Gregorio, M. Giordano, S. Rossi, M. Staffa and B. Siciliano: A WiSARD-Based Tracker for Deformable Objects. Submitted to: IROS 2014, IEEE/RSJ International Conference on Intelligent Robots and Systems.
- [55] B.P.A. Grieco, P.M.V. Lima, M. De Gregorio, F.M.G. Franca, Extracting fuzzy rules from "mental" images generated by modified WiSARD perceptrons. In: 17th European Symposium on Artificial Neural Networks, 2009, Bruges. Proc. of ESANN 2009. Evre, Belgium: d-side, 2009. p. 313-318.
- [56] B.P.A. Grieco, P.M.V. Lima, M. De Gregorio and F.M.G. França, Producing pattern examples from mental images. *Neurocomputing* (Amsterdam), v. 73, p. 1057-1064, 2010.
- [57] A. Hussain, I. Aleksander, L. S. Smith and R. Chrisley, Brain inspired cognitive systems (BICS). *Neurocomputing* 72(4-6): 683-684 (2009)
- [58] D. Johnston, Foreword, in: *Dendrites*, G. Stuart, N. Spruston and M. Häusser, Eds, Oxford University Press, 1999.
- [59] K. Khaki and T. J. Stonham, Face Recognition with Weightless Neural Networks Using the MIT Database, in *Autonomous and Intelligent Systems*, eds. M. Kamel, F. Karray and H. Hagrais, Springer Berlin Heidelberg, pp. 228-233, 2012.
- [60] C. Koch and T. Poggio, Biophysics of Computation: Neurons, Synapses and Membranes, in: *Synaptic Function*, G. M. Edelman, W. E. Gall and W.M. Cowan, John Wiley & Sons, 1987.
- [61] T.B. Ludermir, M.C.P de Souto and W.R. de Oliveira, Weightless Neural Networks: Knowledge-based Inference System. In: Simposio Brasileiro de Redes Neurais SBRN, 2008, Salvador, Bahia. Proceedings of SBRN 2008, 2008.
- [62] W. Martins and N. Allinson, Two improvements for GSN neural networks, *Proc. of the Weightless Neural Networks Workshop*, York, pp.58-63, 1993.
- [63] W. McCulloch and W. Pitts, A logical calculus of the ideas immanent in nervous activity, *Bulletin of Mathematical Biophysics*, 7, pp. 115-133, 1943.
- [64] R.S. Moreira, N.F. Ebecken, A.S. Alves and F.M.G. Franca, Tracking Targets in Sea Surface with the WiSARD Weightless Neural Network. In: BRICS-CCI, 2013, Ipojuca, PE. Proc. of BRICS-CCI & CBIC 2013, 2013. v. 1. p. 1-6.
- [65] J. Mrcic-Flogel, Approaching Cognitive System Design, *Proceedings of the International Conference on Artificial Neural Networks (ICANN 91)*, Helsinki, Vol. 1, pp. 879-883, 1991.
- [66] M.A. Nielsen and I. L. Chuang. Quantum Computation and Quantum Information. Cambridge University Press, 2000.
- [67] W.R. de Oliveira, A. Silva, T.B. Ludermir, A. Leonel, W.R. Galindo and J.C.C. Pereira, Quantum Logical Neural Networks. In: Simposio Brasileiro de Redes Neurais SBRN, 2008, Salvador, Bahia. Proceedings of SBRN 2008, 2008.
- [68] W. R. de Oliveira, Quantum RAM Based Neural Networks. In: European Symposium on Artificial Neural Networks - Advances in Computational Intelligence and Learning, 2009, Bruges, Belgique. European Symposium on Artificial Neural Networks - Advances in Computational Intelligence and Learning, 2009.
- [69] W. R. de Oliveira. ; A. Silva ; T. B. Ludermir ; Vector Space Weightless Neural Networks. ESANN 2014, European Symposium on Artificial Neural Networks, Computational Intelligence and Machine Learning, Bruges, Belgium. (This issue)

- [70] F.A.N.C. Pinto, W.S. Pacheco, R.S. Siqueira and F. M. G. Franca, Comparison between pattern recognition schemes from noise mappings. In: 19th International Congress on Sound and Vibration, 2012, Vilnius. Proc. of ICSV 2012, 2012. v. 4. p. 2745-2752.
- [71] C. B. do Prado, F. M. G. França, E. Costa and L. Vasconcelos, A new intelligent systems approach to 3D animation in television, *Proc. of the 6th ACM international Conference on Image and Video Retrieval*, pp.117-119, 2007.
- [72] C. B. do Prado, F. M. G. França, R. Diacovo and P. M. V. Lima, The Influence of Order on a Large Bag of Words, *Proc. of the 8th International Conference on Intelligent Systems Design and Applications*, IEEE CS Press, v. 1, pp. 432-436, 2008.
- [73] S. Rao and I. Aleksander, A Position Identification and Path Labelling Mechanism for a Neural Model of Visual Awareness. *Cognitive Computation* 2(4): 360-372 (2010)
- [74] S. Rao and I. Aleksander, A depictive neural model for the representation of motion verbs. *Cognitive Processing* 12(4): 395-405 (2011)
- [75] S. Rao and Igor Aleksander, A Neural Mechanism for Function Application in Visual Awareness Models. *International Journal of Computational Intelligence and Applications* 10(3): 249-267 (2011)
- [76] D. E. Rumelhart, G. E. Hinton, J. L. McClelland, A General Framework for Parallel Distributed Processing, in: *Parallel Distributed Processing: Explorations in the Microstructure of Cognition*, Vol.1, MIT Press, 1988.
- [77] A. Silva, W. R. de Oliveira and T.B. Ludermir, Superposition Based Learning Algorithm. In: Brazilian Symposium on Neural Network, 2010, São Bernardo do Campo. Proceedings of Brazilian Symposium on Neural Network. Los Alamitos: IEEE Computer Press, 2010. v. 1.
- [78] A. Silva, W. R. de Oliveira and T.B. Ludermir, A Weightless Neural Node based in a Probabilistic Quantum Memory. In: Brazilian Symposium on Neural Network, 2010, São Bernardo do Campo. Proceedings of Brazilian Symposium on Neural Network. Los Alamitos: IEEE Computer Press, 2010. v. 1.
- [79] A. J. Silva, W. R. de Oliveira and T.B. Ludermir, Classical and superposed learning for quantum weightless neural networks. *Neurocomputing (Amsterdam)*, v. 74, p. 1-10, 2011.
- [80] A. Silva, W. R. de Oliveira and T.B. Ludermir, On the universality of quantum logical neural networks. In: Brazilian Symposium on Neural Networks - SBRN, 2012, Curitiba. Proceedings of the SBRN. Los Alamitos: IEEE Computer Society, 2012. p. 1-6.
- [81] C. M. Soares, C. L. F. da Silva, M. De Gregorio, and F. M. G. França. Uma implementação em software do classificador WISARD (In Portuguese). In V Simpósio Brasileiro de Redes Neurais, vol. 2, p. 225-229, Belo Horizonte, MG, Brazil, December 1998.
- [82] C. R. Souza, F.F. Nobre, P.M.V. Lima LIMA, P. M. V. Lima, R.M. Silva, R.M. Brindeiro and F.M.G. Franca, Recognition of HIV-1 subtypes and antiretroviral drug resistance using weightless neural networks. In: European Symposium on Artificial Neural Networks, Computational Intelligence and Machine Learning, 2012, Bruges. Proc. of ESANN 2012. Brussels: i6doc.com, 2012. v. 1. p. 429-434.
- [83] D.F.P. Souza, H.C.C. Carneiro, F. M. G. Franca and P. M. V. Lima, Rock-paper-scissors WiSARD. In: BRICS-CCI, 2013, Ipojuca, PE. Proc. of BRICS-CCI & CBIC 2013, 2013. v. 1. p. 1-6.
- [84] M. Staffa, S. Rossi, M. De Gregorio and E. Burattini, Thresholds tuning of a neuro-symbolic net controlling a behavior-based robotic system. ESANN 2011
- [85] R. Tallis and I. Aleksander: 'Computer models of the mind are invalid'. *JIT* 23(1): 55-62 (2008)
- [86] J.G. Taylor, Spontaneous behaviour in neural networks, *Journal of Theoretical Biology*, 36, pp. 513-528, 1972.