

Mechanized Irrigation

LOW PRESSURE - HIGH PERFORMANCE™



AGRICULTURAL IRRIGATION | A Hunter Industries Company
Learn More. Visit senninger.com

Senninger®

Mechanized Irrigation



WOBLER®

i-Wob®2 (black)



Flow: 0.8 - 18.35 gpm (182 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet size: Medium

i-Wob®2 (grey)



Flow: 2.24 - 18.35 gpm (509 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet Size: Small

i-Wob®2 (blue)



Flow: 0.8 - 18.35 gpm (182 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet Size: Medium

i-Wob®2 (white)



Flow: 2.51 - 18.35 gpm (570 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet Size: Large

Xi-Wob™ (blue)



Flow: 1.09 - 15.78 gpm (248 - 3584 L/hr)
Pressure: 10 - 15 psi (0.69 - 1.03 bar)
Droplet Size: Medium

Xi-Wob™ (black)



Flow: 2.24 - 15.78 gpm (509 - 3584 L/hr)
Pressure: 10 - 15 psi (0.69 - 1.03 bar)
Droplet Size: Large

Xi-Wob™ (grey)



Flow: 2.24 - 15.78 gpm (509 - 3584 L/hr)
Pressure: 10 - 15 psi (0.69 - 1.03 bar)
Droplet Size: Small

Xcel-Wobler™ TOP



Flow: 0.8 - 14.98 gpm (182 - 3402 L/hr)
Pressure: 10 psi (0.69 bar)
Droplet Size: Large

LDN®

LDN®



Flow: 0.27 - 21.2 gpm (61 - 4815 L/hr)
Pressure: 6 - 20 psi (0.41 - 1.38 bar)
Several deflector pad options including part-circle

LDN® LEPA Bubbler



Flow: 0.27 - 18.35 gpm (61 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Several deflector pad options

LDN® LEPA Shroud™



Flow: 0.27 - 18.35 gpm (61 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Several deflector pad and insert options

LDN® LEPA Wide Spray Bubble



Flow: 0.35 - 5.08 gpm (79 - 1154 L/hr)
Pressure: 6 - 10 psi (0.41 - 0.69 bar)
Several deflector pad options

LDN® Dynamic Drive (top-of-pipe)



Flow: 0.8 - 33.49 gpm (182 - 7606 L/hr)
Pressure: 10 - 50 psi (0.69 - 3.45 bar)
Low and high pressure models

LDN® Dynamic Drive (hose drops)



Flow: 0.8 - 25.94 gpm (182 - 5892 L/hr)
Pressure: 10 - 30 psi (0.69 - 2.07 bar)
Low and high pressure models

LDN® Dynamic Drive (part-circle)



Flow: 1.43 - 8.79 gpm (325 - 1996 L/hr)
Pressure: 10 - 30 psi (0.69 - 2.07 bar)

IMPACT SPRINKLERS

Pivot Master®



Flow: 1.87 - 36.0 gpm (425 - 8177 L/hr)
Pressure: 30 - 60 psi (2.07 - 4.14 bar)

REGULATORS | SPRAYS | COMPONENTS

PRL



Flow: 0.5 - 8 gpm (114 - 1817 L/hr)
Pressure: 6 - 40 psi (0.41 - 2.76 bar)

PSR™2



Flow: 0.5 - 15 gpm (114 - 3407 L/hr)
Pressure: 6 - 50 psi (0.41 - 3.45 bar)

PMR-MF



Flow: 2 - 20 gpm (454 - 4542 L/hr)
Pressure: 6 - 60 psi (0.41 - 4.14 bar)

Filter Regulator



Flow: 0.7 - 16.78 (16 - 3811 L/hr)
Pressure: 6 - 20 psi (0.41 - 1.38 bar)

Super Spray®



Flow: 0.27 - 29.96 gpm (61 - 6805 L/hr)
Pressure: 6 - 40 psi (0.41 - 2.76 bar)
Several deflector pad options

End Spray



Flow: 8.1 - 48.9 gpm (1840 - 11106 L/hr)
Pressure: 10 - 25 psi (0.69 - 1.72 bar)


COMPONENTS

Universal Magnum Weight™



Fits all Senninger sprinklers used on hose drops

Goosenecks



Sgl max flow: 20 gpm (4542 L/hr)
Dbl max flow: 15 gpm (3406 L/hr) per side
Use Truss Rod Hose Slings with 125° models